## NSN 5305-01-221-8700

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-221-8700 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.190 inches **Fastener Length:** Between 0.690 inches and 0.692 inches **Head Style:** Flat chamfer **Head Diameter:** 0.310 inches **Head Height:** 0.160 inches **Shoulder Diameter:** 0.186 inches and 0.187 inches first shoulder **Shoulder Length:** 0.500 inches and 0.502 inches first shoulder **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 **Shoulder Shape:** Round first shoulder Material: Steel comp 303 or steel comp 303 plus x or steel comp 303cu or steel comp 303ma or steel comp 303se or steel comp 416 or steel comp 416 plus x or steel comp 416se or steel comp 430f or steel comp 430fse **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

Fiig: A003b0

No

**Demilitarization:** 

## NSN 5305-01-221-8700

Shoulder Screw - Page 2 of 2



Mil-std (military Standard):

Mil-f-14072 spec.