NSN 5305-01-221-8700

Shoulder Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-221-8700



Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.190 inches

Fastener Length:

Between 0.690 inches and 0.692 inches

Head Style:

Flat chamfer

Head Diameter:

0.310 inches

Head Height:

0.160 inches

Shoulder Diameter:

0.186 inches and 0.187 inches first shoulder

Shoulder Length:

0.500 inches and 0.502 inches first shoulder

Internal Drive Style:

Slot

Thread Diameter:

0.164 inches

Thready Qty Per Inch (tpi):

32

Shoulder Shape:

Round first shoulder

Material:

Steel comp 303 or steel comp 303 plus x or steel comp 303cu or steel comp 303ma or steel comp 303se or steel comp 416 or steel comp 416 plus x or steel comp 416se or steel comp 430f or steel comp 430fse

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-f-14072 military specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

NSN 5305-01-221-8700

Shoulder Screw - Page 2 of 2

Mil-std (military Standard):

Mil-f-14072 spec.

