

View Online at <https://aerobasegroup.com/nsn/5305-01-222-2336>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.688 inches

Fastener Length:

1.687 inches

Head Style:

Knurled no. 4

Head Diameter:

0.750 inches

Head Height:

0.438 inches

Shank Unthreaded Hole Diameter:

0.063 inches and 0.065 inches first hole

First Diameter From Head:

0.281 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

0.999 inches

Internal Drive Style:

Slot

Thread Diameter:

0.375 inches

Thready Qty Per Inch (tpi):

16

Criticality Code Justification:

Zzzy

Distance From Head Largest Bearing Surface To Shank Hole Center:

0.813 inches and 0.937 inches first hole

Externally Relieved Body Diameter Quantity:

1

Special Features:

Head straight knurl

Material:

Steel comp 303

Material Specification:

Astma582 assn standard single material response

Surface Treatment:

Passivate

Special Test Features:

Special quality control testing

Test Data Document:

81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc

Reference Number Differentiating Characteristics:

As differentiated by material which must conform to ships parts control center special quality control provisions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0