## NSN 5305-01-222-9083

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-222-9083

Thread Class:			
3a			
Thread Direction:			
Right-hand			
Thread Length:			
Between 0.386 inches and 0.453 inches			
Fastener Length:			
Between 1.896 inches and 1.943 inches			
Head Style:			
Flat countersunk			
Head Diameter:			
Between 0.464 inches and 0.507 inches			
Grip Diameter:			
Between 0.2485 inches and 0.2495 inches			
Internal Drive Style:			
Offset cruciform (torque set)			
Thread Diameter:			
0.250 inches			
Grip Length:			
Between 1.490 inches and 1.510 inches			
Thready Qty Per Inch (tpi):			
28			
Min. Tensile Strength (psi):			
220000 pounds per square inch			
Countersink Angle:			
Between 99.0 degrees and 101.0 degrees			
Surface Finish:			
32.0 microinches threads			
Special Features:			
Internal drive ribbed			
Material:			
Steel comp h11			
Material Specification:			
Ams6487 assn standard single material response			
Surface Treatment:			
Cadmium or cadmium and chromate			
Surface Treatment Specification:			
Nas672 assn standard 1st treatment response or mil-s-8837, ty2, cl2 military specification 2nd treatment response			
Thread Series Designator:			
Unjf			
Shelf Life:			
N/a			

## NSN 5305-01-222-9083

Close Tolerance Screw - Page 2 of 2



U	nit	Of	Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-8837 spec.