## NSN 5305-01-222-9083

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-222-9083

| Thread Class:   |  |  |  |
|---|--|--|--|
| 3a  |  |  |  |
| Thread Direction:   |  |  |  |
| Right-hand  |  |  |  |
| Thread Length:  |  |  |  |
| Between 0.386 inches and 0.453 inches   |  |  |  |
| Fastener Length:  |  |  |  |
| Between 1.896 inches and 1.943 inches   |  |  |  |
| Head Style:   |  |  |  |
| Flat countersunk  |  |  |  |
| Head Diameter:  |  |  |  |
| Between 0.464 inches and 0.507 inches   |  |  |  |
| Grip Diameter:  |  |  |  |
| Between 0.2485 inches and 0.2495 inches   |  |  |  |
| Internal Drive Style:   |  |  |  |
| Offset cruciform (torque set)   |  |  |  |
| Thread Diameter:  |  |  |  |
| 0.250 inches  |  |  |  |
| Grip Length:  |  |  |  |
| Between 1.490 inches and 1.510 inches   |  |  |  |
| Thready Qty Per Inch (tpi):   |  |  |  |
| 28  |  |  |  |
| Min. Tensile Strength (psi):  |  |  |  |
| 220000 pounds per square inch   |  |  |  |
| Countersink Angle:  |  |  |  |
| Between 99.0 degrees and 101.0 degrees  |  |  |  |
| Surface Finish:   |  |  |  |
| 32.0 microinches threads  |  |  |  |
| Special Features:   |  |  |  |
| Internal drive ribbed   |  |  |  |
| Material:   |  |  |  |
| Steel comp h11  |  |  |  |
| Material Specification:   |  |  |  |
| Ams6487 assn standard single material response  |  |  |  |
| Surface Treatment:  |  |  |  |
| Cadmium or cadmium and chromate   |  |  |  |
| Surface Treatment Specification:  |  |  |  |
| Nas672 assn standard 1st treatment response or mil-s-8837, ty2, cl2 military specification 2nd treatment response |  |  |  |
| Thread Series Designator:   |  |  |  |
| Unjf  |  |  |  |
| Shelf Life:   |  |  |  |
| N/a   |  |  |  |

## NSN 5305-01-222-9083

Close Tolerance Screw - Page 2 of 2



| U | nit | Of | Measure: |
|---|-----|----|----------|
|   |     |    |          |

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-8837 spec.