

View Online at <https://aerobasegroup.com/nsn/5305-01-223-0461>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.2035 inches

Fastener Length:

Between 0.2805 inches and 0.3125 inches

Head Style:

Pan no. 2

Head Diameter:

Between 0.306 inches and 0.322 inches

Head Height:

Between 0.085 inches and 0.096 inches

Washer Quantity:

2

Internal Drive Style:

Slot

Thread Diameter:

0.164 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

55000 pounds per square inch

Secondary Washer Relationship To Primary Washer:

Not identical

Secondary Washer Style:

Flat

Primary Washer Outside Diameter:

0.296 inches

Secondary Washer Outside Diameter:

Between 0.307 inches and 0.317 inches

Primary Washer Style:

Split helical ring

Primary Washer Material Thickness:

0.296 inches

Secondary Washer Material Thickness:

Between 0.013 inches and 0.019 inches

Material:

Steel secondary washer

Material Specification:

Qq-s-636 federal specification single material response or mil-s-7952 military specification single material response secondary washer

Surface Treatment:

Cadmium secondary washer

Surface Treatment Specification:

Qq-p-416 type 2 class 2 federal specification single treatment response

Thread Series Designator:

Unc

Specification Data:

80205-nas720 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-7952 spec.