

View Online at <https://aerobasegroup.com/nsn/5305-01-223-0461>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.2035 inches

**Fastener Length:**

Between 0.2805 inches and 0.3125 inches

**Head Style:**

Pan no. 2

**Head Diameter:**

Between 0.306 inches and 0.322 inches

**Head Height:**

Between 0.085 inches and 0.096 inches

**Washer Quantity:**

2

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.164 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

55000 pounds per square inch

**Secondary Washer Relationship To Primary Washer:**

Not identical

**Secondary Washer Style:**

Flat

**Primary Washer Outside Diameter:**

0.296 inches

**Secondary Washer Outside Diameter:**

Between 0.307 inches and 0.317 inches

**Primary Washer Style:**

Split helical ring

**Primary Washer Material Thickness:**

0.296 inches

**Secondary Washer Material Thickness:**

Between 0.013 inches and 0.019 inches

**Material:**

Steel secondary washer

**Material Specification:**

Qq-s-636 federal specification single material response or mil-s-7952 military specification single material response secondary washer

**Surface Treatment:**

Cadmium secondary washer

**Surface Treatment Specification:**

Qq-p-416 type 2 class 2 federal specification single treatment response

**Thread Series Designator:**

Unc

**Specification Data:**

80205-nas720 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-s-7952 spec.