## NSN 5305-01-223-2636

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-223-2636

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.782 inches and 0.875 inches
Fastener Length:
Between 0.844 inches and 0.875 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.306 inches and 0.313 inches
Head Height:
Between 0.103 inches and 0.118 inches
Internal Drive Style:
Torque set
Thread Diameter:
0.190 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
Between 24.0 rockwell c and 35.0 rockwell c
Screw Material:
Iron alloy 660
Screw Material Specification:
Ams 5737 assn standard single material response
Screw Surface Treatment:
Cadmium and chromate
Screw Surface Treatment Specification:
Qq-p-416, type 2, class 2 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas1101 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

## NSN 5305-01-223-2636

Machine Screw - Page 2 of 2



Fiig:

A500d0