

View Online at <https://aerobasegroup.com/nsn/5305-01-223-2645>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.250 inches

Fastener Length:

0.785 inches

Head Style:

Hexagon

Head Height:

0.100 inches

Width Between Flats:

Between 0.305 inches and 0.312 inches

Internal Drive Style:

Slot

Material Accommodated Thickness:

Between 0.251 inches and 0.312 inches

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Material:

Steel comp 301 fastener or steel comp 302 fastener or steel comp 302b fastener or steel comp 303 fastener or steel comp 303se fastener or steel comp 304 fastener or steel comp 304l fastener or steel comp 305 fastener or steel comp 308 fastener or steel comp 309 fastener or steel comp 309s fastener or steel comp 310 fastener or steel comp 310s fastener or steel comp 314 fastener or steel comp 316 fastener or steel comp 316l fastener or steel comp 317 fastener or steel comp 321 fastener or steel comp 347 fastener or steel comp 348 fastener or steel comp 384 fastener or steel comp 385 fastener

Material Specification:

Qq-a-225/8 federal specification single material response stand-off

Surface Treatment:

Passivate spring

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response spring

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):