NSN 5305-01-223-7667

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-223-7667 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.182 inches and 0.192 inches **Fastener Length:** 0.187 inches **Head Style:** Knurled no. 2 **Head Diameter:** 0.500 inches **Head Height:** Between 0.223 inches and 0.275 inches Point Length: 0.125 inches **Point Diameter:** Between 0.105 inches and 0.120 inches **First Diameter From Head:** Between 0.115 inches and 0.125 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.490 inches and 0.510 inches **Point Style:** Cone **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 **Externally Relieved Body Diameter Quantity: Point Chamfer Angle:** Between 55.0 degrees and 65.0 degrees Material: Steel comp 303 **Material Specification:** Qq-s-764 federal specification single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-f-14072, e300 military specification single treatment response

NSN 5305-01-223-7667

Externally Relieved Body Screw - Page 2 of 2



Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0
Mil-std (military Standard):

Mil-f-14072 spec.