

View Online at <https://aerobasegroup.com/nsn/5305-01-225-2600>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

2.125 inches

Head Style:

Hexagon

Head Height:

0.125 inches

Width Between Flats:

0.250 inches

Point Length:

1.000 inches

Point Diameter:

0.250 inches

Point Style:

Chamfer dog

Internal Drive Style:

W/o internal drive

Thread Diameter:

0.375 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

150000 pounds per square inch

Hardness Rating:

32.0 rockwell c and 38.0 rockwell c

Point Chamfer Angle:

90.0 degrees

Special Features:

Apply protective coating dod-p-16232, type m, cl 2; shoulder in point area 0.750 from end 0.060 in. Length and 0.317 in. Diameter

Material:

Steel comp 1013 or steel comp 1015 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1023 or steel comp 1524 or steel comp 1025 or steel comp 1026 or steel comp 1527 or steel comp 1029 or steel comp 1030 or steel comp 1033 or steel comp 1034 or steel comp 1035 or steel comp 1536 or steel comp 1037 or steel comp 1038 or steel comp 1039 or steel comp 1040 or steel comp 1541

Material Specification:

66 federal standard all material responses

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fig:

A003b0