

View Online at <https://aerobasegroup.com/nsn/5305-01-225-2611>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.332 inches and 0.403 inches

**Fastener Length:**

Between 2.638 inches and 2.668 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

0.506 inches

**Grip Diameter:**

Between 2.2485 inches and 2.2495 inches

**Internal Drive Style:**

Offset cruciform (torque set)

**Thread Diameter:**

0.250 inches

**Grip Length:**

Between 2.240 inches and 2.260 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

36.0 rockwell c and 40.0 rockwell c

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Surface Finish:**

32.0 microinches threads

**Material:**

Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas1580 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0