NSN 5305-01-225-2612

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-225-2612
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.569 inches and 0.619 inches
Fastener Length:
Between 1.267 inches and 1.297 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.5149 inches and 0.5662 inches
Grip Diameter:
Between 0.3735 inches and 0.3745 inches
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.375 inches
Grip Length:
Between 0.678 inches and 0.698 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Countersink Angle:
Between 99.0 degrees and 100.0 degrees
Surface Finish:
32.0 microinches threads
Material:
Iron alloy 660
Material Specification:
Ams5731 assn standard single material response or ams5732 assn standard single material response or ams5737 assn standard single
material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unif

Specification Data:

80205-nas1581 professional/industrial association standard

NSN 5305-01-225-2612

Close Tolerance Screw - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0