

View Online at <https://aerobasegroup.com/nsn/5305-01-225-7708>

**Thread Direction:**

Right-hand

**Thread Length:**

Between 5.0 millimeters and 6.0 millimeters

**Fastener Length:**

6.00 millimeters

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 5.23 millimeters and 5.50 millimeters

**Head Height:**

Between 1.82 millimeters and 2.00 millimeters

**Internal Drive Style:**

Slot

**Thread Diameter:**

3.0 millimeters

**Min. Tensile Strength (psi):**

113000 pounds per square inch

**Thread Pitch In Millimeters:**

0.5

**External Thread Tolerance Class:**

6h

**Screw Material:**

Steel

**Screw Surface Treatment:**

Cadmium and chromate or zinc and chromate or aluminum and chromate

**Screw Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification 1st treatment response or mil-c-87115, cl 1 military specification 2nd treatment response or mil-c-83488, type 2, cl 2 military specification 3rd treatment response

**Thread Series Designator:**

M

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0

**Mil-std (military Standard):**

Mil-c-87115 spec.