NSN 5305-01-225-7726

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-225-7726

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.330 inches and 0.360 inches |
| Fastener Length: |
| Between 1.570 inches and 1.620 inches |
| Head Style: |
| Flat countersunk |
| Head Diameter: |
| Between 0.337 inches and 0.383 inches |
| Grip Diameter: |
| Between 0.1885 inches and 0.1895 inches |
| Internal Drive Style: |
| Cross recess type 1 |
| End Application: |
| Used on sentry f22 aircraft |
| Thread Diameter: |
| 0.190 inches |
| Grip Length: |
| Between 1.240 inches and 1.260 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Countersink Angle: |
| 100.0 degrees |
| Material: |
| Steel comp e4340 or steel comp 8740 |
| Material Specification: |
| Mil-s-5000 military specification 1st material response or mil-s-6049&jdgams 6322 military specification 2nd material response |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Qq-p-416, type 2, cl 2 federal specification single treatment response |
| Thread Series Designator: |
| Unjf |
| Specification Data: |
| 81205-bac20lu3-20 manufacturers standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5305-01-225-7726

Close Tolerance Screw - Page 2 of 2



| Demi | | | |
|------|--|--|--|
| | | | |
| | | | |

Yes - demil/mli

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.