NSN 5305-01-225-7727

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-225-7727

80205-nas1578 professional/industrial association standard

Thread Class:	
3a	
Thread Direction:	
Right-hand	
Thread Length:	
Between 0.378 inches and 0.428 inches	
Fastener Length:	
Between 0.826 inches and 0.856 inches	
Head Style:	
Pan no. 2	
Head Diameter:	
Between 0.477 inches and 0.492 inches	
Head Height:	
Between 0.140 inches and 0.150 inches	
Grip Diameter:	
Between 0.2485 inches and 0.2495 inches	
Internal Drive Style:	
Offset cruciform (torque set)	
Thread Diameter:	
0.250 inches	
Grip Length:	
Between 0.428 inches and 0.448 inches	
Thready Qty Per Inch (tpi):	
28	
Min. Tensile Strength (psi):	
160000 pounds per square inch	
Surface Finish:	
32.0 microinches threads	
Special Features:	
Internal drive ribbed	
Material:	
Iron alloy 660	
Material Specification:	
Ams5731 assn standard single material response or ams5737 assn standard single material response	
Surface Treatment:	
Passivate	
Surface Treatment Specification:	
Qq-p-35 federal specification single treatment response	
Thread Series Designator:	
Unjf	
Specification Data:	
00005 man4570 mentagging lindustrial appropriation at and and	

NSN 5305-01-225-7727

Close Tolerance Screw - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0