## NSN 5305-01-225-7730

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-225-7730
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.569 inches and 0.619 inches
Fastener Length:
Between 0.954 inches and 0.984 inches
Head Style:
Pan no. 2
Head Diameter:
Between 0.722 inches and 0.740 inches
Head Height:
Between 0.206 inches and 0.220 inches
Grip Diameter:
Between 0.3735 inches and 0.3745 inches
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.375 inches
Grip Length:
Between 0.365 inches and 0.385 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Surface Finish:
32.0 microinches threads
Product Name:
Navy special project
Material:
Steel comp 4140 or steel comp e4340 or steel comp 8740
Material Specification:
Mil-s-6049 military specification 1st material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 type 2 class 2 federal specification single treatment response
Thread Series Designator:

Unjf

## NSN 5305-01-225-7730

Close Tolerance Screw - Page 2 of 2



Specification Data:
80205-nas1578 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6049 spec.