## NSN 5305-01-226-4928

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-226-4928 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.125 inches **Fastener Length:** 0.250 inches **Head Style:** Pan **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.070 inches and 0.080 inches First Diameter From Head: 0.070 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.125 inches **Internal Drive Style:** Cross recess type ii **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Stainless steel **Material Specification:** Qq-s-763 federal specification single material response **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-c-13924, class 4 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

Demilitarization:

No

## NSN 5305-01-226-4928

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.