Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-226-4930

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
0.625 inches
Fastener Length:
1.500 inches
Head Style:
Pan
Head Diameter:
Between 0.357 inches and 0.373 inches
Head Height:
Between 0.122 inches and 0.133 inches
First Diameter From Head:
Between 0.140 inches and 0.145 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
0.0875 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.190 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
80000 pounds per square inch
Externally Relieved Body Diameter Quantity:
1
Material:
Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316
Material Specification:
66 federal standard all material responses
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0