NSN 5305-01-226-5927



Socket Head Cap Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-226-5927 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.875 inches **Fastener Length:** Between 2.210 inches and 2.250 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.303 inches and 0.312 inches **Head Height:** Between 0.185 inches and 0.190 inches

Internal Drive Style:

Hexagon

Thread Diameter:

0.190 inches

Width Across Flats:

Between 0.156 inches and 0.159 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

38.0 rockwell c and 45.0 rockwell c

Minimum Yield Strength:

155000 pounds per square inch

Material:

Steel

Material Specification:

Mil-h-6875 military specification single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2 cl 3 federal specification single treatment response

Thread Series Designator:

Unrc

Specification Data:

80205-nas1352 professional/industrial association standard

Shelf Life:

N/a

NSN 5305-01-226-5927

Socket Head Cap Screw - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-h-6875 spec.