NSN 5305-01-226-9063

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-226-9063

View Online at https://aerobasegroup.com/nsn/5305-01-226-9063
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.444 inches and 0.494 inches
Fastener Length:
Between 1.204 inches and 1.234 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.574 inches and 0.637 inches
Shoulder Diameter:
0.3266 inches and 0.3276 inches first shoulder
Shoulder Length:
0.740 inches and 0.760 inches first shoulder
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.312 inches
Thready Qty Per Inch (tpi):
24
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Shoulder Shape:
Round first shoulder
Material:
Steel comp e4340 or steel comp 8740
Material Specification:
Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 assn standard
2nd material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, cl 2 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5305-01-226-9063

Shoulder Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.