

View Online at <https://aerobasegroup.com/nsn/5305-01-227-3210>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.294 inches and 0.375 inches

**Fastener Length:**

Between 0.344 inches and 0.375 inches

**Head Style:**

Pan

**Head Diameter:**

Between 0.205 inches and 0.219 inches

**Head Height:**

Between 0.070 inches and 0.080 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.112 inches

**Thready Qty Per Inch (tpi):**

40

**Min. Tensile Strength (psi):**

80000 pounds per square inch

**Screw Material:**

Steel comp 301 or steel comp 302 or steel comp 303 or steel comp 384 or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 1552 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 1054 or steel comp 1055 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 323 or steel comp 324 or steel comp 347 or steel comp 348 or steel comp 385 or steel comp 302b

**Special Features:**

Finish primed surface with gray epoxy enamel, one coat, per mil-c-22750, color 36231

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0