

View Online at <https://aerobasegroup.com/nsn/5305-01-227-4605>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 1.491 inches and 1.655 inches

Fastener Length:

Between 1.558 inches and 1.588 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.338 inches and 0.381 inches

Grip Diameter:

Between 0.1890 inches and 0.1895 inches

Single Shear Strength:

95000 pounds per square inch

Internal Drive Style:

Tri-wing recess

Thread Diameter:

0.190 inches

Grip Length:

Between 1.240 inches and 1.260 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Iron alloy 660

Material Specification:

Ams 5731 assn standard single material response or ams 5737 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Nas4003 assn standard single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas4503 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0