NSN 5305-01-227-4608

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-227-4608 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.323 inches **Fastener Length:** Between 0.433 inches and 0.463 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.367 inches and 0.373 inches **Head Height:** Between 0.103 inches and 0.108 inches **Grip Diameter:** Between 0.1081 inches and 0.1087 inches Single Shear Strength: 95000 pounds per square inch **Internal Drive Style:** Tri-wing recess **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.115 inches and 0.135 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Steel **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas5003 professional/industrial association standard Shelf Life: N/a

...

Unit Of Measure:

NSN 5305-01-227-4608

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0