NSN 5305-01-227-6382

Externally Relieved Body Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-227-6382 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.520 inches **Fastener Length:** 1.575 inches **Head Style:** Pan **Head Diameter:** Between 0.473 inches and 0.492 inches **Head Height:** Between 0.162 inches and 0.175 inches **First Diameter From Head:** Between 0.161 inches and 0.164 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 1.055 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 348 or steel comp 384 or steel comp comp 385 **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:**

Demilitarization:
No
Fiig:

A003b0