## NSN 5305-01-229-5538

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-229-5538



## Thread Class:

3a

**Thread Direction:** 

Right-hand

#### Thread Length:

Between 2.842 inches and 2.843 inches

#### Fastener Length:

Between 2.859 inches and 2.906 inches

#### **Head Style:**

Dished hexagon

#### Head Height:

Between 0.105 inches and 0.120 inches

#### Width Between Flats:

Between 0.305 inches and 0.314 inches

#### Internal Drive Style:

Cross recess type 1

#### Thread Diameter:

0.190 inches

#### Thready Qty Per Inch (tpi):

32

#### Min. Tensile Strength (psi):

160000 pounds per square inch

#### Screw Material:

Steel comp 4340 or steel comp 8740

#### Screw Material Specification:

Mil-s-5000 military specification single material response or mil-s-6049 military specification single material response or ams6322 assn standard single material response

#### **Screw Surface Treatment:**

Cadmium

#### Screw Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

#### Thread Series Designator:

Unjf

#### **Specification Data:**

80205-nas1801 professional/industrial association standard

#### Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

### Fiig:

A500d0

# NSN 5305-01-229-5538

Machine Screw - Page 2 of 2

### Mil-std (military Standard):

Mil-s-5000 spec.

