## NSN 5305-01-229-5543



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-229-5543 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.968 inches and 1.064 inches **Fastener Length:** Between 0.984 inches and 1.064 inches **Head Style:** Dished hexagon **Head Height:** Between 0.188 inches and 0.203 inches Width Between Flats: Between 0.492 inches and 0.502 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.3750 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Screw Material:** Steel comp 4340 or steel comp 8740 **Screw Material Specification:** Mil-s-5000 military specification single material response or mil-s-6049 military specification single material response or ams6322 assn standard single material response **Screw Surface Treatment:** Cadmium **Screw Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1801 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:** 

Fiig: A500d0

No

**Demilitarization:** 

## NSN 5305-01-229-5543

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-5000 spec.