## NSN 5305-01-229-7955

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-229-7955 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.280 inches **Fastener Length:** 0.660 inches **Head Style:** Knurled no. 1 **Head Diameter:** 0.310 inches **Head Height:** 0.190 inches **First Diameter From Head:** Between 0.090 inches and 0.100 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.380 inches **Point Style:** Cone **Internal Drive Style:** W/o internal drive **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 **Externally Relieved Body Diameter Quantity:** Material: Steel comp 303 or steel comp 303se or steel comp 416 or steel comp 416se or steel comp 430f or steel comp 430fse **Material Specification:** Astm a581 assn standard all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5305-01-229-7955

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0