## NSN 5305-01-229-7956

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-229-7956 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.203 inches **Fastener Length:** Between 0.422 inches and 0.454 inches **Head Style:** Knurled no. 4 **Head Diameter:** Between 0.307 inches and 0.317 inches **Head Height:** Between 0.296 inches and 0.328 inches **First Diameter From Head:** Between 0.073 inches and 0.083 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.224 inches and 0.244 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Straight knurl Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

--

## NSN 5305-01-229-7956

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0