NSN 5305-01-229-9968



Close Tolerance Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-229-9968 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.350 inches and 0.417 inches **Fastener Length:** Between 1.422 inches and 1.469 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.625 inches and 0.635 inches **Grip Diameter:** Between 0.3112 inches and 0.3117 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.312 inches **Grip Length:** Between 1.052 inches and 1.072 inches Width Across Flats: Between 0.1885 inches and 0.1905 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** 36.0 rockwell c and 40.0 rockwell c **Countersink Angle:** 100.0 degrees Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 **Surface Treatment:** Cadmium head

Surface Treatment Specification:

Qq-p-416, type 1 class 3 federal specification single treatment response head

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5305-01-229-9968

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0