NSN 5305-01-230-2432

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-230-2432 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.250 inches **Fastener Length:** 1.000 inches **Head Style:** Hexagon **Head Height:** 0.160 inches Width Between Flats: 0.375 inches Point Length: 0.040 inches First Diameter From Head: 0.140 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.750 inches Point Style: Cone **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): 32 **Externally Relieved Body Diameter Quantity: Point Chamfer Angle:** 120.0 degrees Material: Steel comp 630 **Material Specification:** Ams 5643 assn standard single material response **Surface Treatment:**

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

NSN 5305-01-230-2432

Externally Relieved Body Screw - Page 2 of 2



Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0