## NSN 5305-01-230-3355

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-230-3355 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.220 inches and 0.240 inches **Fastener Length:** Between 0.720 inches and 0.750 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.262 inches and 0.270 inches **Head Height:** Between 0.159 inches and 0.164 inches **First Diameter From Head:** Between 0.110 inches and 0.120 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.480 inches and 0.530 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.164 inches Width Across Flats: Between 0.141 inches and 0.143 inches Thready Qty Per Inch (tpi): 32 **Externally Relieved Body Diameter Quantity:** Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

## NSN 5305-01-230-3355

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0