Socket Head Cap Screw - Page 1 of 2





View Online at https://aerobasegroup.com/nsn/5305-01-230-3362

Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 0.470 inches and 0.562 inches Fastener Length: Between 0.532 inches and 0.562 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.218 inches and 0.226 inches **Head Height:** Between 0.134 inches and 0.138 inches Locking Feature: Pellet threads **Internal Drive Style:** Hexagon **Thread Diameter:** 0.138 inches Width Across Flats: Between 0.109 inches and 0.111 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Plastic polyamide locking feature **Material Specification:** Ams 5731 assn standard single material response or ams 5737 assn standard single material response fastener Surface Treatment: Passivate fastener **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response fastener **Thread Series Designator:** Unrc **Specification Data:** 80205-nas1352 professional/industrial association standard Shelf Life: N/a Unit Of Measure:

NSN 5305-01-230-3362

Socket Head Cap Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

