## NSN 5305-01-230-9894

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-230-9894 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.380 inches **Fastener Length:** Between 1.713 inches and 1.750 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.285 inches and 0.332 inches First Diameter From Head: Between 0.119 inches and 0.123 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 1.370 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 80000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Externally Relieved Body Diameter Quantity: Special Features:** Finish color black Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Material Specification:** 66 federal standard all material responses **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-c-13924 military specification single treatment response **Thread Series Designator:** Unc

**Shelf Life:** N/a

## NSN 5305-01-230-9894

Externally Relieved Body Screw - Page 2 of 2



Unit	Of	Measure:

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.