NSN 5305-01-231-0685

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-231-0685

View Online at https://aerobasegroup.com/nsn/5305-01-231-0685
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.338 inches and 0.388 inches
Fastener Length:
Between 2.973 inches and 3.003 inches
Head Style:
Pan no. 2
Head Diameter:
Between 0.360 inches and 0.374 inches
Head Height:
Between 0.115 inches and 0.125 inches
Grip Diameter:
Between 0.1885 inches and 0.1895 inches
Internal Drive Style:
High-torque
Thread Diameter:
0.190 inches
Grip Length:
Between 2.615 inches and 2.635 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Surface Finish:
32.0 microinches threads
Material:
Iron alloy 660
Material Specification:
Ams5731 assn standard single material response or ams5732 assn standard single material response or ams5737 assn standard single
material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas1578 professional/industrial association standard
Shelf Life:

N/a

NSN 5305-01-231-0685

Close Tolerance Screw - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0