## NSN 5305-01-231-3847

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-231-3847

Thread Class:						
3a						
Thread Direction:						
Right-hand						
Thread Length:						
Between 0.280 inches and 0.361 inches						
Fastener Length:						
Between 0.862 inches and 0.902 inches						
Head Style:						
Pan						
Head Diameter:						
Between 0.464 inches and 0.493 inches						
Head Height:						
Between 0.133 inches and 0.150 inches						
Shoulder Diameter:						
0.246 inches and 0.249 inches first shoulder						
Shoulder Length:						
0.510 inches and 0.520 inches first shoulder						
Internal Drive Style:						
Cross recess type 1						
Thread Diameter:						
0.190 inches						
Thready Qty Per Inch (tpi):						
32						
Min. Tensile Strength (psi):						
125000 pounds per square inch						
Shoulder Shape:						
Round first shoulder						
Material:						
Stainless steel						
Material Specification:						
Mil-s-7839 military specification single material response						
Surface Treatment:						
Cadmium and chromate						
Surface Treatment Specification:						
Qq-p-416, type 2, class 2 federal specification single treatment response						
Thread Series Designator:						
Unjf						
Specification Data:						
80205-nas1298 professional/industrial association standard						
Shelf Life:						
N/a						

N/a

## NSN 5305-01-231-3847

Shoulder Screw - Page 2 of 2



	• -			
In	ıŧ	( )t	Measure	•

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-7839 spec.