NSN 5305-01-231-7393

Thumbscrew - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-231-7393
Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
0.340 inches
Fastener Length:
0.750 inches
Head Style:
Knurled no. 2
Head Diameter:
0.750 inches
Head Height:
0.500 inches
Shoulder Diameter:
0.500 inches first shoulder
Shoulder Length:
0.250 inches first shoulder
Point Style:
Flat
Thread Diameter:
0.138 inches
Thready Qty Per Inch (tpi):
32
Shoulder Shape:
Round first shoulder
Special Features:
Straight knurl head
Material:
Steel comp 303 or steel comp 303ma or steel comp 303 plus x or steel comp 303se or steel comp 416 or steel comp 416 plus x or steel
comp 416se or steel comp 420f or steel comp 420fse or steel comp 430f or steel comp 430fse
Material Specification:
Astm a582 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Mil-f-14072 e300 military specification single treatment response
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5305-01-231-7393

Thumbscrew - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.