NSN 5305-01-231-8464

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-231-8464 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 1.125 inches **Fastener Length:** Between 2.460 inches and 2.500 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.457 inches and 0.469 inches **Head Height:** Between 0.306 inches and 0.312 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.312 inches Width Across Flats: Between 0.250 inches and 0.253 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 170000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 150000 pounds per square inch **Special Features:** Finish color black Material: Steel **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-c-13924, cl 1 military specification single treatment response **Thread Series Designator:** Unrf **Specification Data:**

80205-nas1351 professional/industrial association standard

Shelf Life:

N/a

NSN 5305-01-231-8464

Socket Head Cap Screw - Page 2 of 2



П	Init	7 1+	Measure:
u	,,,,,	v	wicasuic.

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.