

View Online at <https://aerobasegroup.com/nsn/5305-01-231-8937>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.248 inches and 0.278 inches

Fastener Length:

Between 0.424 inches and 0.474 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.190 inches and 0.225 inches

Grip Diameter:

Between 0.1105 inches and 0.1115 inches

Internal Drive Style:

Cross recess type 1

End Application:

Kc-46 tanker

Thread Diameter:

0.112 inches

Grip Length:

Between 0.176 inches and 0.196 inches

Thready Qty Per Inch (tpi):

40

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Special Features:

Faa certified

Material:

Steel comp 4340 or steel comp 8740

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 assn standard 2nd material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.