NSN 5305-01-232-5088

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-232-5088 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.765 inches and 0.858 inches **Fastener Length:** Between 0.907 inches and 0.938 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.322 inches and 0.385 inches **Internal Drive Style:** Torque set **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: Between 36.0 rockwell c and 40.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416 type 2 class 2 federal specification single treatment response **Special Features:** Internal drive ribbed **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1102 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-01-232-5088

Machine Screw - Page 2 of 2



Fiig:

A500d0