NSN 5305-01-232-5599

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-232-5599 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.523 inches and 0.559 inches **Fastener Length:** Between 2.351 inches and 2.371 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.722 inches and 0.740 inches **Head Height:** Between 0.189 inches and 0.204 inches **Locking Feature:** Detent ball grip **Shank Unthreaded Hole Diameter:** 0.106 inches first hole and 0.116 inches first hole **Internal Drive Style:** Slot **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): Distance From Head Largest Bearing Surface To Shank Hole Center: 2.223 inches first hole and 2.243 inches first hole **Surface Finish:** 32.0 microinches grip **Product Name:** Navy special project Material: Iron alloy 660 fastener **Material Specification:** Ams5737 assn standard single material response fastener **Surface Treatment:** Passivate fastener **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response fastener **Thread Series Designator:** Unjf

O.,,.

Shelf Life:

N/a

NSN 5305-01-232-5599

Socket Head Cap Screw - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A003b0