

View Online at <https://aerobasegroup.com/nsn/5305-01-232-6713>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.452 inches and 0.467 inches

**Fastener Length:**

2.710 inches

**Head Style:**

Double chamfer

**Head Diameter:**

0.688 inches

**Head Height:**

0.830 inches

**Locking Feature:**

Detent ball grip

**First Diameter From Head:**

Between 0.374 inches and 0.375 inches

**Second Diameter From Head:**

Between 0.298 inches and 0.308 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

0.380 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

Between 0.493 inches and 0.508 inches

**Internal Drive Style:**

Square

**Thread Diameter:**

0.375 inches

**Width Across Flats:**

Between 0.378 inches and 0.385 inches

**Thready Qty Per Inch (tpi):**

24

**Externally Relieved Body Diameter Quantity:**

1

**Special Features:**

Head design in three section; from top 0.250 in. Length, 0.688 in. Dia., 0.770 in. Length, 0.440 in. Dia., 0.830 in. Length, 0.630 in. Dia.; point shank from threaded end, 1.750 in. Length, 0.249 in. Min. And 0.250 in. Max. Dia.; hole in shank, from head 1.750 in. To center of hole 0.0627 in. Min. And 0.0631 in. Max. Dia. Supplied with plunger and plug

**Material:**

Steel comp 630 spring

**Material Specification:**

Ams5643 assn standard single material response spring

**Surface Treatment:**

Passivate spring

**Surface Treatment Specification:**

Qq-p-416, type 2 class 3 federal specification single treatment response fastener

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0