## NSN 5305-01-232-6720

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-232-6720

Thread Oleans
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.439 inches and 0.516 inches
Fastener Length:
Between 1.329 inches and 1.376 inches
Head Style:
Pan Hand Biometers
Head Diameter:
Between 0.357 inches and 0.373 inches
Head Height:
Between 0.122 inches and 0.133 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.190 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
125000 pounds per square inch
Hardness Rating:
Between 26.0 rockwell c and 32.0 rockwell c
Screw Material:
Steel comp 4037 or steel comp 8630
Screw Material Specification:
Ams 6300 assn standard 1st material response or mil-s-6050 military specification 2nd material response
Screw Surface Treatment:
Cadmium and phosphate
Screw Surface Treatment Specification:
Qq-p-416 type 2 class 3 federal specification single treatment response
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Possilitariantion.
Demilitarization:
No Files
Fiig:
A500d0

## NSN 5305-01-232-6720

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-6050 spec.