

View Online at <https://aerobasegroup.com/nsn/5305-01-232-7954>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.222 inches and 0.355 inches

Fastener Length:

Between 0.344 inches and 0.406 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.249 inches and 0.279 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.138 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

125000 pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Screw Material:

Steel comp 202 or steel comp 302 or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 309 or steel comp 310 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 324 or steel comp 347 or steel comp 403 or steel comp 405 or steel comp 410 or steel comp 414 or steel comp 416 or steel comp 416se or steel comp 420 or steel comp 430 or steel comp 430f or steel comp 430fse or steel comp 431 or steel comp 440a or steel comp 440b or steel comp 440c or steel comp 440f or steel comp 440fse or steel comp 446

Screw Surface Treatment:

Oxide

Screw Surface Treatment Specification:

Mil-f-495 military specification 1st treatment response or mil-f-13924 military specification 2nd treatment response

Color:

Black

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):