NSN 5305-01-233-2004



Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-233-2004 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.183 inches and 0.193 inches **Fastener Length:** 1.063 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.308 inches and 0.316 inches **Head Height:** Between 0.146 inches and 0.166 inches **Shoulder Diameter:** 0.186 inches and 0.187 inches first shoulder **Shoulder Length:** 0.875 inches and 0.877 inches first shoulder **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 **Shoulder Shape:** Round first shoulder **Special Features:** Furnished with undercut Material: Steel comp 203ez or steel comp 303 or steel comp 303 plus x or steel comp 303ma or steel comp 303pb or steel comp 303se or steel comp 416 or steel comp 416 plus x or steel comp 416se or steel comp 430f or steel comp 430fse or steel comp 420f or steel comp 420fse or steel comp 440f **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

No

Unit Of Measure:

Demilitarization:

NSN 5305-01-233-2004

Shoulder Screw - Page 2 of 2



Fiig:

A003b0