## NSN 5305-01-233-3917

Socket Head Cap Screw - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5305-01-233-3917      |
|--|
| Thread Class:  |
| 2a   |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| 0.250 inches   |
| Fastener Length:   |
| 0.250 inches   |
| Head Style:  |
| Pan no. 2  |
| Head Diameter:   |
| Between 0.205 inches and 0.238 inches                              |
| Head Height:   |
| Between 0.070 inches and 0.080 inches                              |
| Locking Feature:   |
| Patch threads  |
| Internal Drive Style:  |
| Cross recess type ii   |
| Thread Diameter:   |
| 0.112 inches   |
| Thready Qty Per Inch (tpi):  |
| 40   |
| Special Features:  |
| Annular recess head with sealing o-ring, resist to hydraulic fluid |
| Material:  |
| Stainless steel fastener   |
| Material Specification:  |
| Mil-s-82496 military specification 1st material response           |
| Surface Treatment:   |
| Passivate fastener   |
| Surface Treatment Specification:                                   |
| Qq-p-35 federal specification 1st treatment response fastener      |
| Thread Series Designator:  |
| Unc  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fila:  |

A003b0

## NSN 5305-01-233-3917

Socket Head Cap Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-82496 spec.