## NSN 5305-01-234-1661

Close Tolerance Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-234-1661



## **Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 0.248 inches and 0.278 inches Fastener Length: Between 0.486 inches and 0.536 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.190 inches and 0.225 inches **Grip Diameter:** Between 0.1105 inches and 0.1115 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Grip Length: Between 0.238 inches and 0.258 inches Thready Qty Per Inch (tpi): 40 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp 4340 or steel comp 8740 Material Specification: Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 assn standard 2nd material response Surface Treatment: Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A003b0

## NSN 5305-01-234-1661

Close Tolerance Screw - Page 2 of 2

Mil-std (military Standard):

Mil-s-5000 spec.

