## NSN 5305-01-234-2539

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-234-2539 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.270 inches **Fastener Length:** 0.630 inches **Head Style:** Flat chamfer **Head Diameter:** 0.270 inches **Head Height:** 0.164 inches **First Diameter From Head:** 0.114 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.360 inches **Point Style:** Flat **Internal Drive Style:** Hexagon **Thread Diameter:** 0.164 inches Width Across Flats: Between 0.141 inches and 0.143 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

--

## NSN 5305-01-234-2539

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0