NSN 5305-01-234-4733

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-234-4733

| Thread Class: |
|--|
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.219 inches and 0.250 inches |
| Fastener Length: |
| Between 0.219 inches and 0.250 inches |
| Head Style: |
| Fillister |
| Head Diameter: |
| Between 0.250 inches and 0.270 inches |
| Head Height: |
| Between 0.141 inches and 0.156 inches |
| Hole Diameter: |
| Between 0.045 inches and 0.050 inches |
| Internal Drive Style: |
| Slot |
| Thread Diameter: |
| 0.164 inches |
| Hole Quantity: |
| 1 |
| Thready Qty Per Inch (tpi): |
| 32 |
| Screw Material: |
| Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 |
| Screw Material Specification: |
| Aisi assn standard all material responses and 66 federal standard all material responses |
| Screw Surface Treatment: |
| Oxide film |
| Screw Surface Treatment Specification: |
| Mil-c-13924 cl4 military specification single treatment response |
| Head Hole Configuration Style: |
| Round |
| Special Features: |
| Make from ms35275-241 |
| Thread Series Designator: |
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5305-01-234-4733

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-c-13924 spec.