Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-234-6348

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.359 inches and 0.391 inches
Fastener Length:
Between 0.922 inches and 0.954 inches
Head Style:
Knurled no. 1
Head Diameter:
0.750 inches
Head Height:
Between 0.234 inches and 0.266 inches
First Diameter From Head:
Between 0.170 inches and 0.180 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
Between 0.553 inches and 0.573 inches
Point Style:
Cone
Internal Drive Style:
Slot
Thread Diameter:
0.250 inches
Thready Qty Per Inch (tpi):
28
Externally Relieved Body Diameter Quantity:
1
Material:
Steel comp 203ez or steel comp 303 or steel comp 303se or steel comp 303ma or steel comp 303cu or steel comp 303 plus x or steel
comp 416 or steel comp 416se or steel comp 416 plus x or steel comp 430f or steel comp 430fse
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Νο

NSN 5305-01-234-6348

Externally Relieved Body Screw - Page 2 of 2

Fiig: A003b0

